

AIRFIX D-E PN16 - prosystemitalia.com

AIRFIX D-E PN16 - Group 2013F



Application

High quality vessels for use in all (potable) water installations. The inside of the Airfix connection flange has a special coating which prevents oxidation.

With replacable bladder

Technical Data

Max. working temperature: 70 °C (EN13831)

Max. working pressure: 16 bar

Approvals

- CE 0045 in according with PED 97/23/EC
- DVGW and WRAS certified
- Accordant to European Directive 2002/16/CE

Type	Capacity [litri]	Ø [mm]	H [mm]	Flange PN16 (2x)
Airfix D-E 50	50	450	836	DN 40
Airfix D-E 80	80	450	1016	DN 40
Airfix D-E 120	120	450	1271	DN 40
Airfix D-E 180	180	550	1227	DN 40
Airfix D-E 240	240	550	1487	DN 40
Airfix D-E 300	300	550	1827	DN 40
Airfix D-E 600	600	750	1840	DN 50
Airfix D-E 800	800	750	2230	DN 50

Type	Capacity [litri]	Ø [mm]	H [mm]	Flange PN16 (2x)
Airfix D-E 1000	1000	750	2730	DN 50
Airfix D-E 1600	1600	1000	2663	DN 80
Airfix D-E 2000	2000	1200	2412	DN 80
Airfix D-E 3000	3000	1200	3312	DN 80

Tipo	Kg	Pezzi per confezione	Codice Articolo
50 L	76	1	14701
80 L	86	1	14801
120 L	101	1	14813
180 L	141	1	14819
240 L	166	1	14825
300 L	196	1	14831
600 L	307	1	14861
800 L	357	1	14881
1000 L	422	1	14911
1600 L	625	1	14917
2000 L	695	1	14921
3000 L	905	1	14931