

**Prosystem Italia Srl**

Via Friuli Venezia Giulia, 15  
30030 Pianiga (VE) Italy  
Tel. +39 041 5101622  
Fax. +39 041 5131351

P. Iva 03470750278  
Reg.Imp. Ve 03470750278  
Cap. Soc. Euro 90.000,00  
REA Padova n° 311219

[www.prosystemitalia.com](http://www.prosystemitalia.com)  
[info@prosystemitalia.com](mailto:info@prosystemitalia.com)



END CAP WITH ECCENTIRC HOLE 300R - [prosystemitalia.com](http://prosystemitalia.com)

## END CAP WITH ECCENTIRC HOLE 300R - Group 300Rz



### Application

Closing cap for a pipe, to connect with a grooved joint. With threaded eccentric hole.

### Technical data

Working pressure: 20 bar up to 8", 12 bar from 10"

Material:

- Body: spheroidal graphite cast iron according to ASTM A536 and ISO 1083.
- Surface treatment: hot galvanized.

| Type [DN] | Diam. G [inch] | Diam. G [mm] | C [mm] | B [mm] |
|-----------|----------------|--------------|--------|--------|
| 50        | 1" 1/2         | 48,3         | 7      | 25     |
| 65        | 2"             | 60,3         | 3      | 25     |
| 80        | 2"             | 60,3         | 9      | 25     |
| 100       | 2"             | 60,3         | 22     | 25     |
| 125       | 2"             | 60,3         | 34     | 25     |
| 150       | 2"             | 60,3         | 48     | 25     |
| 200       | 2"             | 60,3         | 73     | 31     |

### Approval

FM, UL.



| <b>Tipo</b>          | <b>Kg</b> | <b>Pezzi per confezione</b> | <b>Codice Articolo</b> |
|----------------------|-----------|-----------------------------|------------------------|
|                      | 0.43      | 75                          | 300R060048Z            |
| 76,1× 60,3 mm 2"½×2" | 0.59      | 48                          | 300R076060Z            |
| 114,3× 60,3 mm 4"×2" | 1.27      | 27                          | 300R114060Z            |
| 139,7× 60,3 mm 5"×2" | 1.79      | 18                          | 300R139060Z            |
| 168,3× 60,3 mm 6"×2" | 2.4       | 12                          | 300R168060Z            |