


FLEXIBLE COUPLING INOX MOD. F270SS - prosystemitalia.com

FLEXIBLE COUPLING INOX MOD. F270SS - Group F270S



Application

Flexible coupling for stainless steel grooved pipe.

Suitable for joining of the pipes, for sanitary and heating systems, sprinkler systems and steam systems.

Technical Data

Working pressure: 20 bar up 8", 12 bar from 10"

Working temperature: from -34°C to +110°C with EPDM

Material: Stainless steel A4

X [mm]	Y [mm]	Z [mm]	Deflection [degree]	Pipe end separation [mm]
54	100	44	3,8	2,2
62	108	44	3	2,2
68	114	44	2,9	2,2
81	128	45	2,5	2,2
98	144	46	2,2	2,2
111	161	47	2	2,6
140	189	48	1,8	2,6
167	227	49	1,6	2,6
197	256	49	1,6	2,6
254	322	59	1,3	4,9
310	378	59	1	4,9
363	430	59	0,8	4,9

Tipo	Kg	Pezzi per confezione	Codice Articolo
33,7 mm 1"	0.58	1	F270034SS4
42,4 mm 1" ¹ / ₄	0.63	1	F270042SS4
48,3 mm 1" ¹ / ₂	0.67	1	F270048SS4
60,3 mm 2"	0.87	1	F270060SS4
76,1 mm 2" ¹ / ₂	1.02	1	F270076SS4
88,9 mm 3"	1.08	1	F270089SS4
114,3 mm 4"	1.65	1	F270114SS4
139,7 mm 5"	2.29	1	F270139SS4
168,3 mm 6"	2.78	1	F270168SS4
219,1 mm 8"	4.86	1	F270219SS4
273,0 mm 10"	8	1	F270273SS4
323,9 mm 12"	9.26	1	F270324SS4