


RIDUZIONE 241 - prosystemitalia.com

RIDUZIONE 241 - Gruppo 241P



Impiego

Riduzione concentrica per tubi scanalati in acciaio.

Dati tecnici

Pressione di esercizio: 20 bar.

Caratteristiche costruttive

Corpo: ghisa ASTM A536

Trattamento superficiale: verniciato colore rosso RAL 3000.

DN	D x d ["]	D x d [mm]	L [mm]
32 x 25	1" 1/4 x 1"	42,4 x 33,7	64
40 x 25	1" 1/2 x 1"	48,3 x 33,7	64
40 x 32	1" 1/2 x 1" 1/4	48,3 x 42,4	64
50 x 25	2" x 1"	60,3 x 33,7	58
50 x 32	2" x 1" 1/4	60,3 x 42,4	58
50x40	2" x 1" 1/2	60,3 x 48,3	58
65x32	2" 1/2 x 1" 1/4	76,1 x 42,4	58
65x40	2" 1/2 x 1" 1/2	76,1 x 48,3	58
65x50	2" 1/2 x 2"	76,1 x 60,3	58
80 x 32	3" x 1" 1/4	88,9 x 42,4	64
80 x 40	3" x 1" 1/2	88,9 x 48,3	64
80x50	3" x 2"	88,9 x 60,3	64
80x65	3" x 2" 1/2	88,9 x 76,1	64
100x50	4" x 2"	114,3 x 60,3	65
100x65	4" x 2" 1/2	114,3 x 76,1	65
100x80	4" x 3"	114,3 x 88,9	65
125x65	5" x 2" 1/2	139,7 x 76,1	65
125x80	5" x 3"	139,7 x 88,9	65
125x100	5" x 4"	139,7 x 114,3	65

150 x 50	6"X2"	168,3 x 60,3	75
150 x 65	6"X2"1/2	168,3 x 76,1	75
150X80	6"X3"	168,3 x 88,9	75
150X100	6"X4"	168,3 x 114,3	75
150X125	6"X5"	168,3 x 139,7	65
200X100	8"X4"	219,1 x 114,3	85
200X125	8"X5"	219,1 x 139,7	85
200X150	8"X6"	219,1 x 168,3	85
250X200	10"X8"	273,0 x 219,1	85
300x250	12"X10"	323,9 x 273,0	90

Certificazioni

FM, UL.



Tipo	Kg	Pezzi per confezione	Codice Articolo
273,0x168,3 mm 10"x6"	4	6	241P273168
114,3X88,9 mm 4"X3"	1.45	24	241114089C
139,7X88,9 mm 5"x3"	1.7	15	241139089C
139,7x114x3 mm 5"x4"	1.92	15	241139114C
168,3x139,7 mm 6"x5"	2.46	12	241168139C
139,7x 76,1 mm 5"x2 ½"	1.7	15	241P139076
42,4x 33,7 mm 1"¼x1"	0.53	128	241P042034
139,7x 88,9 mm 5"x3"	1.7	15	241P139089
48,3x 33,7 mm 1"½x1"	0.53	1	241P048034
139,7x114,3 mm 5"x4"	1.92	15	241P139114
48,3x 42,4 mm 1"½x1"¼	0.53	110	241P048042
168,3x 60,3 mm 6"x2"	2.14	20	241P168060
60,3x 33,7 mm 2"x1"	0.53	88	241P060034
168,3x 76,1 mm 6"x2 ½"	2.17	20	241P168076
60,3x 42,4 mm 2"x1"¼	0.53	80	241P060042
168,3x 88,9 mm 6"x3"	2.18	20	241P168089
60,3x 48,3 mm 2"x1"½	0.56	75	241P060048
168,3x114,3 mm 6"x4"	1.27	20	241P168114
76,1x 42,4 mm 2"½x1"¼	0.63	63	241P076042
168,3x139,7 mm 6"x5"	1.13	12	241P168139
76,1x 48,3 mm 2"½x1"½	0.64	63	241P076048
76,1x 60,3 mm 2"½x2"	0.74	63	241P076060
88,9x 42,4 mm 3"x1"¼	0.8	45	241P089042

Tipo	Kg	Pezzi per confezione	Codice Articolo
88,9× 48,3 mm 3"×1"½	0.8	45	241P089048
88,9× 60,3 mm 3"×2"	0.8	45	241P089060
88,9× 76,1 mm 3"×2"½	0.94	36	241P089076
114,3× 48,3 mm 4"×1"½	1.22	27	241P114048
114,3× 60,3 mm 4"×2"	1.22	27	241P114060
114,3× 76,1 mm 4"×2"½	1.28	27	241P114076
114,3× 88,9 mm 4"×3"	1.45	27	241P114089