

RIDUZIONE 241 - prosystemitalia.com

RIDUZIONE 241 - Gruppo 241Z



Impiego

Riduzione concentrica per tubi scanalati in acciaio.

Dati tecnici

Pressione di esercizio: 20 bar.

Materiale:

- Corpo: ghisa ASTM A536;
- Trattamento superficiale: zincato a caldo.

DN	D x d ["]	D x d [mm]	L [mm]
32 x 25	1" 1/4 x 1"	42,4 x 33,7	64
40 x 25	1" 1/2 x 1"	48,3 x 33,7	-
40 x 32	1" 1/2 x 1" 1/4	48,3 x 42,4	64
50 x 25	2" x 1"	60,3 x 33,7	64
50 x 32	2" x 1" 1/4	60,3 x 42,4	64
50x40	2" x 1" 1/2	60,3 x 48,3	64
65x32	2" 1/2 x 1" 1/4	76,1 x 42,4	64
65x40	2" 1/2 x 1" 1/2	76,1 x 48,3	64
65x50	2" 1/2 x 2"	76,1 x 60,3	64
80 x 32	3" x 1" 1/4	88,9 x 42,4	-
80 x 40	3" x 1" 1/2	88,9 x 48,3	-
80x50	3" x 2"	88,9 x 60,3	64
80x65	3" x 2" 1/2	88,9 x 76,1	64
100x50	4" x 2"	114,3 x 60,3	70
100x65	4" x 2" 1/2	114,3 x 76,1	70
100x80	4" x 3"	114,3 x 88,9	70
125x65	5" x 2" 1/2	139,7 x 76,1	74
125x80	5" x 3"	139,7 x 88,9	74
125x100	5" x 4"	139,7 x 114,3	74

150 x 50	6"X2"	168,3 x 60,3	-
150 x 65	6"X2"1/2	168,3 x 76,1	-
150X80	6"X3"	168,3 x 88,9	-
150X100	6"X4"	168,3 x 114,3	-
150X125	6"X5"	168,3 x 139,7	-
200X100	8"X4"	219,1 x 114,3	100
200X150	8"X6"	219,1 x 168,3	100
250X200	10"X8"	273,0 x 219,1	159
300x250	12"X10"	323,9 x 273,0	-

Certificazioni

FM, UL.



Tipo	Kg	Pezzi per confezione	Codice Articolo
139,7x 76,1 mm 5"x2 ½"	1.7	15	241P139076Z
139,7x114,3 mm 5"x4"	1.92	15	241P139089Z
139,7x114,3 mm 5"x4"	1.92	15	241P139114Z
48,3x 42,4 mm 1"½x1"¼	0.53	50	241P048042Z
168,3x 76,1 mm 6"x2 ½"	2.17	20	241P168076Z
76,1x 48,3 mm 2"½x1"½	0.64	63	241P076048Z
76,1x 60,3 mm 2"½x2"	0.74	63	241P076060Z
88,9x 42,4 mm 3"x1"¼	0.8	1	241P089042Z
88,9x 48,3 mm 3"x1"½	0.8	45	241P089048Z
60,3x 48,3 mm 2"x1"½	0.56	75	241P060048Z
88,9x 60,3 mm 3"x2"	0.8	45	241P089060Z
88,9x 76,1 mm 3"x2"½	0.94	36	241P089076Z
114,3x 76,1 mm 4"x2"½	1.28	27	241P114060Z
114,3x 76,1 mm 4"x2"½	1.28	27	241P114076Z
114,3x 88,9 mm 4"x3"	1.45	27	241P114089Z
139,7x 76,1 mm 5"x2"½	1.72	15	241139076Z
168,3x 60,3 mm 6"x2"	2.27	12	241168060Z
168,3x 88,9 mm 6"x3"	2.18	20	241P168089Z
168,3x114,3 mm 6"x4"	2.39	20	241P168114Z
168,3x139,7 mm 6"x5"	2.46	12	241P168139Z
219,1x168,3 mm 8"x6"	4.53	10	241P219168Z
273,0x219,1 mm 10"x8"	9.03	8	241P273219Z
329,3x273,0 mm 12"x10"	0	1	241P324273Z