


# ADATTATORE AD ANGOLO WK F



The set WKA F is used to simulate a beam flange with a width of 180 mm on siFramo profiles. It is intended for the connection of third-party pipe shoes. With the help of additional sets, guided supports and fixed points can be realized from sliding pipe shoes.

## 2 Angle Adapters WKA F2 Threaded Stud M12 x 2654 Self Forming Screw FLS F

Angle adapters must be attached to both sides of the siFramo profile with 2 Formlock screws each. If necessary, shorter threaded studs from the external guide set can be replaced by the studs included in the scope of delivery. Note: When using an end support, the distance  $e_2$  must be taken into account. For square end support distances are 200 mm and 220 mm and for octagonal end supports 150 mm and 180 mm, depending on the profile used.

Type	B[mm]	L[mm]	H[mm]	b x l[mm]	e[mm]
WKA F 80	50	180	80	11 x 20	180
WKA F 100	40	180	100	11 x 20	180

Type	F <sub>x</sub> [kN]	F <sub>y</sub> [kN]	F <sub>z</sub> [kN]
WKA F 80	±14	±6	±12
WKA F 100	±14	±6	±12

Note: These values only apply in conjunction with Sikla components. When using third-party systems, the load specifications of the used guide or fixed point sets must be taken into account.

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

info@prosystemitalia.com  
prosystemitalia.com

Material:	Steel, HCP
-----------	------------

Codice	Nome	Peso	Numero di pezzi
117412	ADATTATORE AD ANGOLO WKA F 80	2.97	-
117413	ADATTATORE AD ANGOLO WKA F 100	3.29	-

**PROSYSTEM ITALIA SRL**

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)