



# PERFORATED STRAP



## APPLICATION

For suspension of pipes, without precise dimensions. For installations without special mounting requirements. The plastic type is particularly suitable for damp locations and for the support of copper pipes.

## TECHNICAL DATA

Max adm. load:

- 17 mm: 0,5 kN

- 19 mm: 0,5 kN

Working temperature:

- Galvanized type: up to + 250°C

- Plasticized type: - 40°C up to + 95°C

Codice	Nome	Peso	Numero di pezzi
120874	17×6,4 mm zincata	0.89	1
120883	26×1,0 mm zincata	1.8	1

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)

Codice	Nome	Peso	Numero di pezzi
121015	19x7,0 mm plastificata	0.97	1

---

**PROSYSTEM ITALIA SRL**

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)