




FLANGE SCREW SCR FLA HCP



APPLICATION

Type M10 x 15 allows fixation of channels by means of Drive Plug AN, without exceeding the max. permissible screw-in depth or to go under the min. screw-in depth required.

Type M10 x 25 is the ideal connecting part for two Channels 41.

Versions "TT" are self-forming screws. Type M10 x 55 is applicable for fixing components with thickness of max. 41 mm to "Framo 80" system.

INSTALLATION

The maximum admissible tightening torque strictly has to be observed.

TECHNICAL DATA

M10 x 15 and M10 x 25

Drive: Internal hexagon SW 6

TT M10 x 25 and TT M10 x 55

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

max. adm. tightening torque: 20 Nm (max. adm.)

Drive: Torx-T50

Material: Steel, HCP.

Type	Length[mm]
M10 x 15	15
M10 x 25	25
TT M10 x 25	25
TT M10 x 30	30

Codice	Nome	Peso	Numero di pezzi
198353	M10×25 mm SW 6	0.02	-
110503	M10×25 mm TX50	0.02	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com