

HEIGHT ADJUSTER HRS P



APPLICATION

Suitable for all M&E services. May be fixed directly to the ceiling (anchor) or in a suitable channel. Especially advantageous due to the suspension unit in the upper section of the height adjuster, since it enables the pipes to move in all directions.

SCOPE OF DELIVERY

Pre-assembled component, no loose parts.

INSTALLATION

The upper part of the base component can be used as a tool for screwing in the suspending bolt. Then the bolt only has to be tightened with an open-ended spanner. After mounting, the base component rests freely mobile and rotatable on the rounded bolt head. Fixing a locking nut against the cup nut secures the height adjusted.

TECHNICAL DATA

Material: Base component cast iron, all components galvanised.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Max. perm. working load: 4.0 kN

Max. swinging angle: 7°

Type	Connection to system	Connection to building structure	Adjustment height
P M8	M8	M8 x 22	25 mm
P M10	M10	M10 x 22	25 mm

Codice	Nome	Peso	Numero di pezzi
151519	HRS P M 8 0 - 25 mm	0.06	25
151528	HRS P M10 0 - 25 mm	0.08	25

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com