



CHANNEL CONNECTOR SK-L HCP



APPLICATION

Element for connecting channels. The multiple bearing of the channel is to be secured. The channel connector should not be used between the last two bearing points. In combination with channel > 41/21 the admissible limit has to be respected.

INSTALLATION

Position the Channel Connector on the back of the channel and bolt together the channel ends (through the channel slots) by means of each two self forming screws FLS F 80.

TECHNICAL DATA

Max. adm. limit/ flexion: 300 Nm

Channel height hmax: 62 mm

Overall length: 180 mm

For channel 41.

Material: Steel S235 JR, HCP.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
198971	SK-L	0.36	10
198973	SK-L	0.36	10

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com