

# FISSAGGIO CHIMICO EPOSSIDICO



## APPLICATION



- For structural fixing and consolidation of wooden floors
- Can be used on wood and on constantly damp surfaces
- Can be used in water immersion
- Excellent mechanical and thermal characteristics
- Very low shrinkage, usable even when the diameter of the hole is much higher than the diameter of the bar
- Excellent adhesive power, usable in smooth / diamond-coated / cored holes
- Very high chemical resistance, usable in highly aggressive atmospheres
- Without styrene

## CERTIFICATES

- Seismic performance category C1: Resistance to cyclic loads in a gap of 0.5 mm
- Seismic performance category C2: Resistance to cyclic loads in a variable slot up to 0.8 mm with definition of maximum slip-off
- OPTION 1 For cracked concrete
- TR 023 Certified for use with post-installed

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)

reinforcing bars according to Eurocode 2 • Certified Diamond for use in cored holes



Codice	Nome	Peso	Numero di pezzi
190810		0.35	12

**PROSYSTEM ITALIA SRL**

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)