



RUBBER-METAL-COMBINATION ELEMENT GMT



APPLICATION

The Rubber-Metal Combination Element GMT suppresses vibrations originating from various systems. Such vibrations generated by the system (such as motors, boilers..) are normally transmitted as sound to the environment via rigid building structures. The mounting situation does not affect the efficiency of the Rubber-Metal Combination Element GMT, this element may also be applied as a horizontal stop buffer.

SCOPE OF DELIVERY

1 Set = 4 elements

Each element is accompanied by two hexagon nuts.

TECHNICAL DATA

Type	Maximum load F_{max} [kN]	Mean spring constant c [kN/mm]
M12	5.0	2.2

Temperature range: -30°C up to +70°C

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Material:

- Sound absorption insert: Natural rubber, 57+/-5° Shore;
- Metal parts: Steel, electro-galvanised.

Codice	Nome	Peso	Numero di pezzi
117090	GMT M12 Conf. da 4 pz	1.14	1
193983	AKE M8	0.09	25

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com