


BEAM CONNECTION K25



APPLICATION

Suitable for the construction of self-supporting structures.

ASSEMBLY

The plates must be connected with the profile 41 through T-nuts and bolts M10 or M12 M10 or M12 x 30 x 30.

Be careful to choose the profile according to the loads to be supported.

TECHNICAL DATA

The plate's dimensions follow these standard (any differences from the standard are highlighted):

Thickness : 10 mm

Ø hole: 13,5 mm

Distance between hole and ends: 20 mm

Width: 41 mm

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Hot galvanized HCP.

Codice	Nome	Peso	Numero di pezzi
126715	K25 a trave	0.43	25

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com