


SAFETY STRAP SL VDS



APPLICATION

Support for vertical pipes of NB 100, 125 and 150 - one bracket for three sizes!

Preferably used in combination with Pipe Clamp Stabil D-A or, if sound absorption is required, with Stabil D-A with Lining (see below).

Adjustable in two horizontal directions, thus ensuring an exact and tension-free run of vertical pipes.

In case SFK Brackets from pipe manufactures are used, rubber rings are added as insulation.

SCOPE OF DELIVERY

Partly pre-assembled. Two M10 bolts and two flange nuts for fixing the pipe clamp are included in loose form.

Supplied without pipe clamp. See table below for suitable clamp.

INSTALLATION

Distance between wall and pipe:

NB 100 (SML 110): min. 5 mm - max. 72 mm

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

NB 125 (SML 135): min. 5 mm - max. 53 mm

NB 150 (SML 160): min. 5 mm - max. 40 mm

TECHNICAL DATA

Material: Steel, cold-worked, electro-galvanised

Max. adm. load (pressure): 2,0 kN

Codice	Nome	Peso	Numero di pezzi
105110	SFK	1.1	5

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com