



# SAFETY STRAP SL VDS



## APPLICATION

Support for vertical pipes of NB 100, 125 and 150 - one bracket for three sizes!

Preferably used in combination with Pipe Clamp Stabil D-A or, if sound absorption is required, with Stabil D-A with Lining (see below).

Adjustable in two horizontal directions, thus ensuring an exact and tension-free run of vertical pipes.

In case SFK Brackets from pipe manufactures are used, rubber rings are added as insulation.

## SCOPE OF DELIVERY

Partly pre-assembled. Two M10 bolts and two flange nuts for fixing the pipe clamp are included in loose form.

Supplied without pipe clamp. See table below for suitable clamp.

## INSTALLATION

Distance between wall and pipe:

NB 100 (SML 110): min. 5 mm - max. 72 mm

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)

NB 125 (SML 135): min. 5 mm - max. 53 mm

NB 150 (SML 160): min. 5 mm - max. 40 mm

## TECHNICAL DATA

Material: Steel, cold-worked, electro-galvanised

Max. adm. load (pressure): 2,0 kN

Codice	Nome	Peso	Numero di pezzi
105110	SFK	1.1	5

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)