

# SPEED NUT NT CC 27



## APPLICATION

In particular useful for installation in vertical channels or where access is difficult.

Further advantages:

- Can be used in all channels 27/27 and 27/15, independent of the channel's height;
- No getting stuck on bolt heads when sliding in the channel;
- No appearance of settlement after tightening.

## SCOPE OF DELIVERY

Channel Nut and Spring are tightly connected.

## INSTALLATION

After inserting the Speed Nut into the channel opening, exert a slight axial pressure. This will cause the nut to turn to the right and engage into the channel. De-installation simply requires the nut to be turned to the left and pulled free. Installation and de-installation do not require tools and may be repeated several times.

Tighten the part to be connected - that's it!

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)

## TECHNICAL DATA

Fz = 1.5 kN

Material:

- Channel nut: Steel, class 5.6, electro-galvanised;
- Spring washer: Sheet metal spring steel, rustproof.

Codice	Nome	Peso	Numero di pezzi
195956	M 6	0.01	100
195949	M 8	0.01	100
117358	M10	0.01	100

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)