



# FIXING BRACKET MW S



## APPLICATION

Designed for general mounting purposes as a direct lateral attachment link integrated in binding and bridging beams of concrete or wood, and for similar applications. It may serve as a connecting bracket for framework structures consisting of channels.

Types 60/30/90 and 90/60/90 are designed for attachment of pipes to wooden truss according to VdS CEA-standard 15.2.2.

## TECHNICAL DATA

Material: Angle steel profile, electro-galvanised.

Type	Working load [kN]	B [mm]	b [mm]	d [mm]	s [mm]
45/30/90°	3.5	30	13	11	-
70/40/90°	2.0	40	17/35	10,5	-
60/40/90°	7.5	40	20	13	-
90/60/90°	7.5	40	15	13	50

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)

Note: for Sprinkler systems, application of 60/30/90 and 90/60/90 to wooden truss.

Single Bracket with wooden screw                      Double Bracket with threaded bolt                      "d"  
depending on NB: ≤ NB 50: 2 x 6 mm > NB 50 ≤ DN 100: 2 x 8 mm > NB 100 ≤ DN 150: 2 x  
10 mm



Codice	Nome	Peso	Numero di pezzi
115380	S 45/30	0.07	50
115399	S 60/40	0.17	25
114820	S 90/60	0.26	25

**PROSYSTEM ITALIA SRL**

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)