



END SUPPORT WBD SS



APPLICATION

In combination with a channel, End Support WBD ss is particularly suitable:

- for setting up support structures attached to walls, floors and ceilings;
- as a base for frame structures.

INSTALLATION

Normally, two anchors grouped opposite to each other and along the load axis are sufficient. Only in exceptional cases (e.g. high props in frameworks) four anchors are required.

Tightening torque 40 Nm.

Suitable for Stainless steel channels with width 41 mm up to height ≤ 62 mm.

TECHNICAL DATA

Type	Suitable for channel	A [mm]	s [mm]	B [mm]	b [mm]	h [mm]	C [mm]
41/41-62	41/41 bis 41/62	135	6	100	25	11	125

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

The permissible maximum vertical load for ceiling mounting structures fixed by way of at least one traversing bolt (class 8.8) amounts to 7.0 kN. Material: Stainless steel A4 Working load for wall mounting with channel 41/41 and two anchors of the mentioned load class:

Restrictions $\sigma_{perm} \leq 160 \text{ N/mm}^2$ $f_{perm} \leq L/100$ for $L > 300 \text{ mm}$ $f_{perm} \leq 3 \text{ mm}$ for $L = 200 \dots 300 \text{ mm}$
Anchor load classes A = 1.5 kN B = 2.5 kN C = 3.5 kN D = 6.0 kN E = 9.0 kN



Codice	Nome	Peso	Numero di pezzi
193631	WBD 41/41-62 A4	0.9	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com