


PIPE SHOE LD-HV



APPLICATION

Pipe Shoe - Dual Base

For pipes on suitable surfaces. Height-adjustable in steps of 2.5 mm. When resting on steel beams, a minimum flange width of 80 mm is recommended.

SCOPE OF DELIVERY

The upper part and the two lower parts are bolted together allowing height adjustment. The slide plates are fixed to the lower parts. In order to reduce the spacings of the lugs the pipe clamps from DN 350 are rotated by 45° (see illustration).

INSTALLATION

To guarantee that both sliding plates rest correctly, both webs must be adjusted to exactly the same height.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

TECHNICAL DATA

Type	Height Has delivered [mm]	Height Hrange [mm]	B [mm]DN 200 - 300	B [mm]DN 350 - 600
LD - HV 90	90	88.5 ... 113.5	285	325
LD - HV 150	150	116 ... 168.5	285	325
LD - HV 200	200	171 ... 223.5	285	325

Tightening torque screw connections:

Clamping bolts	tightening torque[Nm]	height adjustment	tightening torque[Nm]
DN 200	50	bolts in the bar	80
DN 250 - 600	60	bolts in the bar	80

Dimensions:

- Metal plate: L = 250 mm
- Slide plate incl.: L = 256 mm

Material:

- Metal parts: Steel, HCP;
- Bolts, Nuts: Steel, HCP;
- Slide plate: Polyamide 6.0, glass fibre reinforced, black.

Media temperature tf : -20 to +300° C (if tf > 270°C, remove slide plate).

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

For dimensions and load charts, please refer to the following pages:

APPROVALS

Certification of quality TUV-Rheinland nr.102793.



Note: HV 200 - minimum quantity and delivery time on request.

Codice	Nome	Peso	Numero di pezzi
112398	LD - HV 90 DN 200	11.9	-
112399	LD - HV 90 DN 250	14.52	-
112400	LD - HV 90 DN 300	15.7	-
110098	LD - HV 90 DN 350	16.6	-
110099	LD - HV 90 DN 400	19	-
110100	LD - HV 90 DN 500	22.4	-
110101	LD - HV 90 DN 600	25.1	-
112401	LD - HV 150 DN 200	13.24	-
112402	LD - HV 150 DN 250	15.92	-
112403	LD - HV 150 DN 300	17	-
110102	LD - HV 150 DN 350	18.1	-
110103	LD - HV 150 DN 400	20.4	-
110104	LD - HV 150 DN 500	24.1	-
110105	LD - HV 150 DN 600	26.4	-
112404	LD - HV 200 DN 200	14.32	-
112405	LD - HV 200 DN 250	16.86	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
112406	LD - HV 200 DN 300	18.02	-
110106	LD - HV 200 DN 350	19	-
110107	LD - HV 200 DN 400	21.4	-
110108	LD - HV 200 DN 500	24.8	-
110109	LD - HV 200 DN 600	27.5	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com