

PIECE BRASS TO



APPLICATION

Universal use for anchor light loads. The product is a piece of brass, therefore is resistant to corrosion and is a low conductor of electricity.

Characteristics:

- For anchor light
- Application of solid materials such as concrete, solid brick and stone;

TECHNICAL DATA

Material: brass.

Type	M6	M8	M10	M12
Adm. load (traction) C20/25 [kN]	0,85	1,5	2,5	3,5
Span $S \geq$ [mm]	60	65	70	75
Charact. edge distance $C \geq$ [mm]	40	45	50	55
Min tickness material [mm]	35	40	45	50
\varnothing tip [mm]	8	10	12	15

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Type	M6	M8	M10	M12
Min depth insertion \geq [mm]	28	35	40	45

Type	Length[mm]	Maxi screw-in depth [mm]
M6	22	15
M8	27,5	18
M10	32	22
M12	38	21

Codice	Nome	Peso	Numero di pezzi
112665	TO M 6	0.01	200
112670	TO M 8	0.01	100
112675	TO M10	0.01	100
112680	TO M12	0.13	100

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com