


# CLAMPING UNIT KL



## APPLICATION

Used for assembling double channels made from Channels with slot pattern III or IV, i.e. with a minimum material thickness of 2.5 mm.

This system could be used for pre-assembly in a workshop also.

When a torque wrench is required in order to ensure that the static values indicated on page 3-7 are achieved.

Attention: These values are only guaranteed when using our Channels.

## SCOPE OF DELIVERY

Consists of forming plate, pressure plate and a hexagon socket bolt M8 (DIN 7991)

## INSTALLATION

Max. spacing between connecting points is 500 mm, with one point at each end of the channel section. Required number of Clamping Units: channel 2m = 5 pcs., channel 6m = 13 pcs.

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)

For channel 41/21/2,0 no connecting elements, like channels nuts, etc. could be placed directly above the connectors.

Torque:  $M = 25 \text{ Nm}$

## TECHNICAL DATA

Material: Malleable cast iron, electro-galvanised.

Codice	Nome	Peso	Numero di pezzi
118055	KL 1	0.11	50

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)