


HOLDING BRACKET HK SS



APPLICATION

Safety element for channels to be used instead of simple washers. The Holding Bracket prevents the edges along the opening of the channels from bending, and ensures optimum load distribution.

Suitable for single and double channels.

When loads are imposed along the channels, 41 Holding Brackets provide for additional safety due to embossed teeth, which bite into the channel.

TECHNICAL DATA

Material: Stainless steel A4.

| Type | Suitable for SIKLACHannels of width [mm] | Bore[mm] |
|-------|--|----------|
| 41/10 | 41 | 11 |
| 41/12 | 41 | 13 |
| 41/16 | 41 | 17 |

| Codice | Nome | Peso | Numero di pezzi |
|--------|------|------|-----------------|
|--------|------|------|-----------------|

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

| Codice | Nome | Peso | Numero di pezzi |
|--------|----------|------|-----------------|
| 178634 | 41/10 A4 | 0.07 | 50 |
| 178643 | 41/12 A4 | 0.08 | 50 |
| 178652 | 41/16 A4 | 0.07 | 50 |

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com