

AIRFIX D-E PN16



APPLICATION

High quality vessels for use in all (potable) water installations. The inside of the Airfix connection flange has a special coating which prevents oxidation.

With replacable bladder

TECHNICAL DATA

Max. working temperature: 70 °C (EN13831)

Max. working pressure: 16 bar

APPROVALS

- CE 0045 in according with PED 97/23/EC
- DVGW and WRAS certified
- Accordant to European Directive 2002/16/CE

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Type	Capacity [litri]	Ø [mm]	H [mm]	Flange PN16 (2x)
Airfix D-E 50	50	450	836	DN 40
Airfix D-E 80	80	450	1016	DN 40
Airfix D-E 120	120	450	1271	DN 40
Airfix D-E 180	180	550	1227	DN 40
Airfix D-E 240	240	550	1487	DN 40
Airfix D-E 300	300	550	1827	DN 40
Airfix D-E 600	600	750	1840	DN 50
Airfix D-E 800	800	750	2230	DN 50
Airfix D-E 1000	1000	750	2730	DN 50
Airfix D-E 1600	1600	1000	2663	DN 80
Airfix D-E 2000	2000	1200	2412	DN 80
Airfix D-E 3000	3000	1200	3312	DN 80

Codice	Nome	Peso	Numero di pezzi
14701	50 L	76	-
14801	80 L	86	-
14813	120 L	101	-
14819	180 L	141	-
14825	240 L	166	-
14831	300 L	196	-
14861	600 L	307	-
14881	800 L	357	-
14911	1000 L	422	-
14917	1600 L	625	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
14921	2000 L	695	-
14931	3000 L	905	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com