

# AIRFIX D



## APPLICATION

For use in potable water or fresh water installations.

The inside of the Airfix vessel has a special coating which prevents oxidation. The composition of the diaphragm has been made for this range in such a way that there will be no variation in smell, colour or taste. The famous Flexcon clench ring construction allows the water section to be coated before assembly.

The Airfix D is fitted with a special synthetic full flow through device which eliminates the formation of unwanted bacteria.

## TECHNICAL DATA

Max. working temperature: 70 °C (EN13831)

Max. working pressure: 8-10 bar

Pre-charge pressure: 4 bar

| Type       | Pre-charge[bar] | Max working pressure [bar] | ø[mm] | H [mm] | Connection |
|------------|-----------------|----------------------------|-------|--------|------------|
| Airfix D 8 | 4               | 10                         | 245   | 301    | 3/4"       |

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)

| Type        | Pre-charge[bar] | Max working pressure [bar] | ø[mm] | H [mm] | Connection |
|-------------|-----------------|----------------------------|-------|--------|------------|
| Airfix D 12 | 4               | 10                         | 286   | 334    | 3/4"       |
| Airfix D 18 | 4               | 10                         | 328   | 325    | 3/4"       |
| Airfix D 25 | 4               | 10                         | 358   | 378    | 3/4"       |
| Airfix D 35 | 4               | 8                          | 396   | 437    | 3/4"       |

## APPROVALS

- CE 0045 in according with PED 97/23/EC
- DVGW
- Accordant to European Directive 2002/16/CE

| Codice | Nome       | Peso | Numero di pezzi |
|--------|------------|------|-----------------|
| 14259  | 8 L PN 10  | 4.1  | 50              |
| 14349  | 12 L PN 10 | 5.2  | 36              |
| 14459  | 18 L PN 10 | 6.2  | 24              |
| 14559  | 25 L PN 10 | 8.1  | 18              |
| 14659  | 35 L PN 8  | 9.9  | 18              |

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)