

AIRFIX A



APPLICATION

For use in potable water or fresh water installations.

The inside of the Airfix vessel has a special coating which prevents oxidation. The composition of the diaphragm has been made for this range in such a way that there will be no variation in smell, colour or taste. The famous Flexcon clench ring construction allows the water section to be coated before assembly.

The Airfix A is fitted with a synthetic flow through device in a standard T-piece (included) which eliminates the formation of unwanted bacteria.

TECHNICAL DATA

Max. working temperature: 70 °C (EN13831)

Max. working pressure: 8-10 bar

Pre-charge pressure: 4 bar

APPROVALS

- CE 0045 in according with PED 97/23/EC

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

- DVGW

- Accordant to European Directive 2002/16/CE

Codice	Nome	Peso	Numero di pezzi
24259	8 L PN 10	3.7	50
24349	12 L PN 10	4.8	36
24459	18 L PN 10	5.9	24
24559	25 L PN 10	7.7	18
24659	35 L PN 8	9.7	18
24749	50 L PN 8	12.1	-
24809	80 L PN 8	15	12

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com