

END CAP 300



APPLICATION

Closing cap for a pipe, to connect with a grooved joint.

TECHNICAL DATA

Working pressure: 20 bar up to 8", 12 bar from 10".

Material:

- Body: spheroidal graphite cast iron according to ASTM A536 and ISO 1083.- Surface treatment: hot galvanized.

APPROVAL

FM, UL.



PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
300042Z	42,4 mm 1" ¹ / ₄	0.16	250
300048Z	48,3 mm 1" ¹ / ₂	0.21	185
300060Z	60,3 mm 2"	0.43	150
300076Z	76,1 mm 2" ¹ / ₂	0.59	105
300089Z	88,9 mm 3"	0.76	72
300114Z	114,3 mm 4"	1.27	45
300139Z	139,7 mm 5"	1.76	27
300168Z	168,3 mm 6"	2.55	20
300219Z	219,1 mm 8"	5.56	14
300273Z	273,0 mm 10"	8	8
300324Z	323,9 mm 12"	-	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com