


Y-STRAINER MOD. FILTER Y



APPLICATION

Y strainer for vertical or horizontal installation. Grooved connection. Technical data Working pressure PN16 Working temperature: - 10°C + 110°C Basket Hole diameters Size 2" to 5" hole Ø1,6 mm, free flow area 33% Size 6" to 8" hole Ø3,0 mm, free flow area 40%. Caratteristiche costruttive Body EN - JS1050, ASTM A536 65-45-12 Cover EN-JS1050, ASTM 536 65-45-12 Plug EN-JS1050, ASTM A536 65-45-12 Gasket Teflon/graphite Red painted

Ø D	H [mm]	L [mm]	Plug
60,3 mm	175	225	½"
76,1 mm	215	285	1"
88,9 mm	219	318	1"
114,3 mm	254	375	1½"
139,7 mm	322	448	2"
168,3 mm	365	502	2"
219,1 mm	462	640	2"



PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
CFY139C		-	1
FY060	60,3 mm 2"	4.2	1
FY076		7.6	1
FY089		8.2	1
FY114		12	1
FY139		22	1
FY168	168,3 mm 6"	32.7	1
FY219		55	1
GFY060		0.05	-
GFY076		0.05	-
GFY089		0.05	-
GFY114		0.05	-
GFY139		0.05	-
GFY168		0.05	-
GFY219		0.05	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com