

END CAP WITH ECCENTIRC HOLE 300R



APPLICATION

Closing cap for a pipe, to connect with a grooved joint. With threaded eccentric hole.

TECHNICAL DATA

Working pressure: 20 bar up to 8", 12 bar from 10"

Material:

- Body: spheroidal graphite cast iron according to ASTM A536 and ISO 1083.- Surface treatment: hot galvanized.

Type [DN]	Diam. G [inch]	Diam. G [mm]	C [mm]	B [mm]
50	1" 1/2	48,3	7	25
65	2"	60,3	3	25
80	2"	60,3	9	25
100	2"	60,3	22	25
125	2"	60,3	34	25
150	2"	60,3	48	25

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Type [DN]	Diam. G [inch]	Diam. G [mm]	C [mm]	B [mm]
200	2"	60,3	73	31

APPROVAL

FM, UL.



Codice	Nome	Peso	Numero di pezzi
300R060048Z		0.43	75
300R076060Z	76,1× 60,3 mm 2"½×2"	0.59	48
300R114060Z	114,3× 60,3 mm 4"×2"	1.27	27
300R139060Z	139,7× 60,3 mm 5"×2"	1.79	18
300R168060Z	168,3× 60,3 mm 6"×2"	2.4	12

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com