


# CHECK VALVE VR



## APPLICATION

The check valves meet the requirements of the "water hammer". The valves VR can be installed in horizontal or vertical position (flow upwards only). Grooved ends allow a rapid and easy installation, which can be performed with two grooved couplings model R270P.

## TECHNICAL DATA

Working pressure: PN16. Working temperature: from -10°C to +120°C (EPDM)

Materials Body: ductile iron A-536 65-45-12, EN-JS1050; Disc: EPDM coated Seat: Stainless Steel AISI 316, BS970 316S16 Spring: Stainless Steel AISI 304, BS 970 304S15 Shaft: Stainless Steel AISI 420, ASTM BS970 420S37 Gasket: EPDM Shaft Plug: Brass Surface treatment: epoxy painting red RAL 3000.

DN	Ø est. [inch]	Ø est. [mm]	A [mm]	B [mm]	C [mm]
50	2"	60,3	99	36	47
65	2½"	76,1	99	53	57
80	3"	88,9	108	54	68
100	4"	114,3	254	76	99
125	5"	139,7	267	111	114
150	6"	168,3	292	105	127
200	8"	219,1	356	130	154

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)

Codice	Nome	Peso	Numero di pezzi
VR139		14.5	1
VR219		38	1

**PROSYSTEM ITALIA SRL**

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)