


CHECK VALVE VR



APPLICATION

The check valves meet the requirements of the "water hammer". The valves VR can be installed in horizontal or vertical position (flow upwards only). Grooved ends allow a rapid and easy installation, which can be performed with two grooved couplings model R270P.

TECHNICAL DATA

Working pressure: PN16. Working temperature: from -10°C to +120°C (EPDM)

Materials Body: ductile iron A-536 65-45-12, EN-JS1050; Disc: EPDM coated Seat: Stainless Steel AISI 316, BS970 316S16 Spring: Stainless Steel AISI 304, BS 970 304S15 Shaft: Stainless Steel AISI 420, ASTM BS970 420S37 Gasket: EPDM Shaft Plug: Brass Surface treatment: epoxy painting red RAL 3000.

DN	Ø est. [inch]	Ø est. [mm]	A [mm]	B [mm]	C [mm]
50	2"	60,3	99	36	47
65	2½"	76,1	99	53	57
80	3"	88,9	108	54	68
100	4"	114,3	254	76	99
125	5"	139,7	267	111	114
150	6"	168,3	292	105	127
200	8"	219,1	356	130	154

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
VR139		14.5	1
VR219		38	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com