


# ADATTATORE A FLANGIA 7012 PN 16



## APPLICATION

Connection to flange.

## TECHNICAL DATA

Working pressure: 20 bar  
Working temperature: from -34°C to +110°C with EPDM  
Material:- Body: spheroidal graphite cast iron according to ASTM A536 and ISO 1083- Surface treatment: red painted RAL 3000.- Gasket: EPDM type E according to ISO 6182, FM 1920 and UL 213.

Bolts: tempered bolts, round head with oval neck. Heavy series nuts in carbon steel according to ASTM A183.

## APPROVAL

FM, UL.

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)

Codice	Nome	Peso	Numero di pezzi
7012060	60,3 mm 2"	1.4	18
7012076	76,1 mm 2"½	2.1	12
7012089	88,9 mm 3"	2.4	10
7012114	114,3 mm 4"	3.5	10
7012139	139,7 mm 5"	4.2	17
7012168	168,3 mm 6"	4.5	7
7012219	219,1 mm 8"	7.5	4
7012273	273,0 mm 10"	11	5
7012324	323,9 mm 12"	12	-
7012073	ADATTATORE A FLANGIA VERNICIATO 2"½ 73	2.1	12

**PROSYSTEM ITALIA SRL**

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)