

LUBRICANT



APPLICATION

Special silicone grease (of the dimethylpolysiloxane type) for high and low temperatures (-40 ° C to + 200 ° C). In addition to the excellent water repellency and excellent resistance to oxidation, excellent adhesiveness is retained: the characteristics require to face the formation of a longer lasting lubricating film resistant to the action of water. This grease is classified as a lubricant H 1, ie an acceptable product as a lubricant, release agent or an anti-rust protective agent which, during use, may come into accidental contact with food without causing any harmful pollution.

TECHNICAL DATA

Gradation 5000 Appearance Pasta of white ice color Basic fluid Pure silicon oil, dimethylpolysiloxane type Viscosity base oil at 25 ° CASTM D 445 350 cSt 5.000 Penetration worked

60 double strokes ASTM D 217 220 - 250 mm / 10

Drop point ASTM D 566 Not measurable Electrical stiffness 12 kV / mm Operating temperature - 40 ° C ÷ + 200 ° C

[DN]	Q.ty (grams)
32	1,5
40	2,0
50	2,5
65	3,0

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

[DN]	Q.ty (grams)
80	3,5
100	4,5
125	6,0
150	7,5
200	9,0
250	12,0
300	16,0

Codice	Nome	Peso	Numero di pezzi
GR110		1	1
GR100	LUBRIFICANTE SILICONICO 100 GRAMMI	0.1	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com