

CURVA 90P



APPLICATION

Elbow connection for grooved pipe steel. Allow the connection of the pipe by a 90° elbow.

TECHNICAL DATA

Working pressure: 20 bar up to 8".

Body: spheroidal graphite cast iron according to ASTM A536 and ISO 1083. Surface treatment: red painted RAL 3000.

NB	ext. Ø [inch]	ext. Ø [mm]	L [mm]
32	1" 1/4	42,2	60
40	1" 1/2	48,3	60
50	2"	60,3	70
65	2" 1/2	76,1	76
80	3"	88,9	86
100	4"	114,3	102
125	5"	139,7	122
150	6"	168,3	140

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

200	8"	219,1	160
250	10"	273	
300	12"	323,9	225

APPROVAL

FM, UL.



Codice	Nome	Peso	Numero di pezzi
90P034	33,7 mm 1"	0.29	120
90P042	42,4 mm 1"¼	0.45	60
90P048	48,3 mm 1"½	0.54	60
90P060	60,3 mm 2"	0.99	43
90P076	76,1 mm 2"½	1.34	36
90P089	88,9 mm 3"	1.63	21
90P114	114,3 mm 4"	2.86	12
90P139	139,7 mm 5"	4.28	6
90P168	168,3 mm 6"	5.92	3
90P219		12.7	1
90P273		23.3	1
90P324		33.4	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com