

TEST AND DRAIN VALVE



APPLICATION

Test valve and outlet system of 1". With orifice inspected 1/2".

TECHNICAL DATA

Connection 1"

Thread: NPT

K Factor: 80

Brass body, chrome plated brass ball, Teflon gasket

Working pressure: 20bar

| Type | PORT | A | B | C | D | H |
|------|------|------|-----|------|------|-----|
| 1" | 2,7 | 12,8 | 6,8 | 13,6 | 11,2 | 4,8 |

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

| Codice | Nome | Peso | Numero di pezzi |
|--------|---------|------|-----------------|
| 943099 | G1" K80 | 0.3 | 1 |
| 943103 | G1" K80 | 0.3 | 1 |
| 943104 | G1" K80 | 0.3 | 1 |
| 943105 | G1" K80 | 0.3 | 1 |
| 943107 | G1" K80 | 0.3 | 1 |
| 943106 | G1" K80 | 0.3 | 1 |
| 943108 | G1" K80 | 0.3 | 1 |
| 943109 | G1" K80 | 0.3 | 1 |

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com