


# GATE VALVE VS NRS



## APPLICATION

Gate valve are organ of interception of pipelines carrying water pressure.

They are frequently used in pumping station or in fire fighting system.

## TECHNICAL DATA

Connections: EN1092-2 PN10/16, ANSI B16.1 Class 125, BS 5163 type A&B

Valvola a saracinesca a cuneo gommato SF secondo standard DIN 3352, DIN 3202-1-F4, EN558-1 Serie 14

Works with handwheel

Working pressure PN16 / Class 125

Working temperature: from -10°C to 120°C

Yoke and galnd follower: ductile iron ASTM 536 65-45-12, EN-JS1050

Wedge: ductile iron, core fully encapsulated with EPDM

Wedge nut: brass ASTM B16 C36000, EN 2874 CZ 124

Stem: stainless steel AISI 420

### PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)

O-Ring: EPDM

Gasket: EPDM

Handwheel: grey cast iron ASTM A536 65-45-12

Coating: electrostatically applied red epoxy resin

Codice	Nome	Peso	Numero di pezzi
VS089	DN 80 3"	25	1
VS168	DN 150 6"	46	1

**PROSYSTEM ITALIA SRL**

Via Friuli venezia Giulia, 15  
30030 Pianiga - Venezia - Italy  
T +39.041.510.1622  
F +39.041.5131351

P.IVA 03470750278  
Reg.Imp. Ve 03470750278  
Cap.soc. € 90.000,00  
REA Padova n° 311219

[info@prosystemitalia.com](mailto:info@prosystemitalia.com)  
[prosystemitalia.com](http://prosystemitalia.com)