


PRESSURE SWITCH MOD. PMU-3 E PMU-10



APPLICATION

Device that promptly reports the operation of activating remote alarm. Enables or disables other equipment. Equipped with Nc contact (normally closed) and Na (Normally Open). This device is adjustable pressure.

TECHNICAL DATA

Temperature range: 0°C up to + 80°C water; - 25°C up to + 100°C compressed air

Voltage: Max 250V-AC/DC.

Operating pressure: Max 16 bar.

Material:

- Cover: PA trasparente;
- Diaphragm: CR with textile reinforcement;
- Housing: GD-Al Si12, sheet steel galvanized.

APPROVALS

Certificated VdS.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com



Codice	Nome	Peso	Numero di pezzi
792183	PMU 3	0.2	1
810564	PMU 10	0.2	-

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com