


PRESSURE SWITCH PMA-3



APPLICATION

Device that promptly reports the operation of activating remote alarm. Enable or disable electrical contacts depending on whether we have achieved a minimum or maximum pressure. Equipped with Nc contact (normally closed) and Na (Normally Open). This pressure switch PMA-3 is used for warning stations and is not adjustable.

TECHNICAL DATA

Temperature range: 0°C up to + 80°C water; - 25°C up to + 100°C compressed air

Voltage: Max 250V-AC/DC.

Operating pressure: Max 16 bar.

Material:

- Cover: PA trasparente;
- Diaphragm: CR with textile reinforcement;
- Housing: GD-Al Si12, sheet steel galvanized.

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

APPROVALS

Certificated FM and VdS.



Codice	Nome	Peso	Numero di pezzi
116512	PMA 3	0.2	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com