



APPLICATION

Fire preventing system made by a stainless steel structure which can be opened for an easier mounting, also after the installation of the pipe. On exposure to heat from a fire (at the temperature of 150°C) they rapidly expand inwards to squeeze the collapsing plastic pipe until the aperture is completely sealed. The collar provides a fire resistance EI 120 both wall and slab.

ADVANTAGES

Rapid installation thanks to the tab closure. Seal against the passage of fumes, gases, flames and heat. You may install the collar into the wall in case of not enough space.

TECHNICAL DATA

Material: stainless steel and intumescent material (mineral fiber and graphite).

Codice	Nome	Peso	Numero di pezzi
156040	DN 40-65	0.5	1
156041	DN 40	0.5	1
156050	DN 50	0.5	1
156080		0.6	1
156090	DN 75-90	0.7	1
156100	DN 100-110	0.8	1
156125	DN 125	0.9	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com

Codice	Nome	Peso	Numero di pezzi
156140	DN 140-160	1	1
156200	DN 200	1.2	1
156250	DN 250	1.4	1
156300	DN 315	-	1

PROSYSTEM ITALIA SRL

Via Friuli venezia Giulia, 15
30030 Pianiga - Venezia - Italy
T +39.041.510.1622
F +39.041.5131351

P.IVA 03470750278
Reg.Imp. Ve 03470750278
Cap.soc. € 90.000,00
REA Padova n° 311219

info@prosystemitalia.com
prosystemitalia.com