


PIPE LOOP RSL N - prosystemitalia.com

PIPE LOOP RSL N - Group 1115



Application

For pipeline installations of fixed fire extinguishing systems, mainly used for sprinkler systems.

Scope of delivery

Pipe Loop with rounded edges. Flange nuts and cup nuts are included in loose form.

Technical Data

Material: Steel, galvanised as per DIN EN 10346.

Type	NB	Nominal load [kN]	Connection	D [mm]	H [mm]
33,7	1"	2,0	M10	34	65
42,4	1" 1/4	2,0	M10	43	65
48,3	1" 1/2	2,0	M10	49	70
60,3	2"	2,0	M10	61	79
76,1	2" 1/2	3,5	M10	77	98
88,9	3"	3,5	M10	90	113
114,3	4"	3,5	M10	115	142
139,7	5"	5,0	M12	142	153
168,3	6"	5,0	M12	170	184
219,1	8"	8,5	M16	221	236

Approvals

FM and VdS (No. G4850025) approved.



Tipo	Kg	Pezzi per confezione	Codice Articolo
33,7 1"	0.06	100	102126
42,4 1 ¼"	0.06	50	102135
48,3 1 ½"	0.06	50	102144
60,3 2"	0.07	50	102153
76,1 2 ½"	0.14	25	102320
88,9 3"	0.16	25	102339
114,3 4"	0.19	25	102357
139,7 5"	0.22	25	102375
168,3 6"	0.26	25	102393
219,1 8"	0.56	10	102409