
Prosystem Italia Srl
Via Friuli Venezia Giulia, 15
30030 Pianiga (VE) Italy
Tel. +39 041 5101622
Fax. +39 041 5131351

P. Iva 03470750278
Reg.Imp. Ve 03470750278
Cap. Soc. Euro 90.000,00
REA Padova n ° 311219

www.prosystemitalia.com
info@prosystemitalia.com

DUCTING ANGLE LUW A - Group 1601



Application
For suspension of pipes, without precise dimensions. For installations without special mounting requirements. The plastic type is particularly suitable for damp locations and for the support of copper pipes.

Technical data
Max adm. load:
17 mm: 0,5 kN
19 mm: 0,5 kN
Working temperature
Galvanized type: up to + 250°C
Plasticized type: - 40°C up to + 95°C

Type	Connection	Width x thickness [mm]	Length [mm]
A-L	M8/M10	35 x 2	35/85
A-Z	M8/M10	35 x 2	35/46/38
A-SL	M8/M10	35 x 2	35/85
A-SZ	M8/M10	35 x 2	35/46/38

Tipo	Kg	Pezzi per confezione	Codice Articolo
	0.09	100	189893
SZ	0.09	100	189902
A-L	0.06	100	110496
A-Z	0.06	100	110498
A-SL	0.06	100	110497
A-SZ	0.06	100	110499