
Prosystem Italia Srl
Via Friuli Venezia Giulia, 15
30030 Pianiga (VE) Italy
Tel. +39 041 5101622
Fax. +39 041 5131351

P. Iva 03470750278
Reg.Imp. Ve 03470750278
Cap. Soc. Euro 90.000,00
REA Padova n ° 311219

www.prosystemitalia.com
info@prosystemitalia.com

STABIL D-2G/-3G SS W/LINING - Group 1741



Application

For the installation of pipes required for all M&E services in industrial, residential and public buildings.

Particularly suitable for soundproof pipe installation according to DIN 4109.

Scope of delivery

Two-piece pipe clamp with clamping bolts and nuts (supplied loose).

Installation

Suitable for single-point mounting either directly by means of a threaded rod or by connecting to a Threaded Tube up to 1" using an adapter.

Technical Data

Material:

- Pipe clamp: Stainless steel A4;

- Sound absorption lining: SBR/EPDM, black (see section "RUBBER PROFILE SAL SBR/EPDM" for technical data).

Size range [mm]	Max. perm. working load [kN]	Tightening torque [Nm]	Thread connection	Material W x th [mm]	B [mm]
18 - 20	1.5	3	2G	25 x 3	77
21 - 24	1.5	3	2G	25 x 3	84

25 - 29	1.5	3	2G	25 x 3	87
31 - 35	1.5	3	2G	25 x 3	95
38 - 42	1.5	3	2G	25 x 3	102
46 - 50	1.5	3	2G	25 x 3	109
51 - 55	1.5	3	2G	25 x 3	115
58 - 63	1.5	3	2G	25 x 3	123
74 - 78	2.0	5	2G	30 x 3	147
86 - 90	2.0	5	3G	30 x 3	160
100 - 106	2.0	5	3G	30 x 3	176
108 - 114	2.0	5	3G	30 x 3	184
133 - 140	4.0	10	3G	40 x 4	229
158 - 168	4.0	10	3G	40 x 4	257
198 - 207	6.0	20	3G	40 x 4	304
210 - 219	6.0	20	3G	40 x 4	316

Tipo	Kg	Pezzi per confezione	Codice Articolo
18 - 20 mm	0.16	50	172703
21 - 24 mm ½''	0.18	50	172712
25 - 29 mm ¾''	0.19	50	172721
31 - 35 mm 1''	0.2	50	172730
38 - 42 mm 1 ¼''	0.22	50	172739
46 - 50 mm 1 ½''	0.24	50	172748
51 - 55 mm	0.25	50	172757
58 - 63 mm 2''	0.27	50	172766
74 - 78 mm 2 ½''	0.39	25	172775
86 - 90 mm 3''	0.46	25	172784
100 - 106 mm	0.49	25	173162
108 - 114 mm 4''	0.49	25	172793
133 - 140 mm 5''	1.03	10	172802
158 - 168 mm 6''	1.14	10	172811
198 - 207 mm	1.5	10	172820
210 - 219 mm 8''	1.54	10	172829