


DUO CLAMP SRS SS - prosystemitalia.com

DUO CLAMP SRS SS - Group 1722



Application

Two-piece clamp with thread connection M8 or M10 for the installation of pipelines.

Scope of delivery

Supplied with two bolts particularly pre-screwed on one side and therefore ready for immediate installation. The clamping bolt on the open side is retained by a plastic washer, thus preventing any accidental unscrewing.

Technical Data

Size range [mm]	For pipe [NB]	Max. perm. working load [kN]	Tightening torque [Nm]	Thread connection	Material W x th [mm]
13 - 18	1/4" + 3/8"	0,6	2	M8	20 x 1.5
19 - 22	1/2"	0,6	2	M8	20 x 1.5
27 - 30	3/4"	0,6	2	M8M8	20 x 1.5
32 - 36	1"	0,6	2	M8	20 x 1.5
40 - 44	1 1/4"	0,6	2	M8	20 x 1.5
48 - 54	1 1/2"	0,6	2	M8	20 x 1.5
60 - 66	2"	0,6	2	M8	20 x 1.5
68 - 73	-	0,6	2	M8	20 x 1.5
75 - 80	2 1/2"	2,5	2	M10	25 x 2.0
84 - 89	3"	2,5	2	M10	25 x 2.0
102 - 108	-	2,5	2	M10	25 x 2.0
110 - 115	4"	2,5	2	M10	25 x 2.0
129 - 140	5"	2,5	2	M10	25 x 2.5
159 - 169	6"	2,5	2	M10	25 x 2.5

The recommended load is calculated using specific statistical methods relating to break load and is designed to restrict deflection to 1.5 mm or 2 % of the maximum applicable clamping diameter.

Material: Stainless steel A4 .

Tipo	Kg	Pezzi per confezione	Codice Articolo
13 - 18 mm ¼"-3/8"	0.04	100	170587
19 - 22 mm ½"	0.05	100	170602
27 - 30 mm ¾"	0.05	100	170611
32 - 36 mm 1"	0.05	100	170620
40 - 44 mm 1 ¼"	0.06	50	170639
48 - 54 mm 1 ½"	0.07	50	170648
60 - 66 mm 2"	0.08	50	170657
68 - 73 mm	0.09	1	173342
75 - 80 mm 2 ½"	0.15	25	170666
84 - 89 mm 3"	0.16	25	170675
102 - 108 mm	0.19	25	173351
110 - 115 mm 4"	0.2	25	170684
129 - 140 mm 5"	0.26	25	110882
159 - 169 mm 6"	0.31	25	110883