


DUO CLAMP SRS SS W/LINING - prosystemitalia.com

DUO CLAMP SRS SS W/LINING - Group 1722E



Application

Two-piece pipe clamp with thread connection M8 or M10 and sound absorption lining for the installation of pipelines.

Scope of delivery

Supplied with two bolts pre-screwed on one side and therefore ready for immediate installation. The clamping bolt on the open side is retained by a plastic washer, thus preventing any accidental unscrewing.

Technical Data

Size range For pipe [mm] [NB]	Max. perm. working load [kN]	Tightening torque [Nm]	Thread connection	Material W x th [mm]
12 - 15 1/4"	0,6	2	M8	20 x 1.5
15 - 19 3/8"	0,6	2	M8	20 x 1.5
20 - 23 1/2"	0,6	2	M8	20 x 1.5
25 - 28 3/4"	0,6	2	M8	20 x 1.5
32 - 35 1"	0,6	2	M8	20 x 1.5
40 - 45 1 1/4"	0,6	2	M8	20 x 1.5
48 - 52 1 1/2"	0,6	2	M8	20 x 1.5
52 - 58 -	0,6	2	M8	20 x 1.5
60 - 64 2"	0,6	2	M8	20 x 1.5
67 - 72 -	2,5	2	M10	25 x 2.0
73 - 80 2 1/2"	2,5	2	M10	25 x 2.0
86 - 91 3"	2,5	2	M10	25 x 2.0
102 - 108 -	2,5	2	M10	25 x 2.0
110 - 115 4"	2,5	2	M10	25 x 2.5

135 - 143	5"	2,5	2	M10	25 x 2.5
149 - 161	-	2,5	2	M10	25 x 2.5
162 - 170	6"	2,5	2	M10	25 x 2.5

Material:

- Pipe clamp: Stainless steel A4;

- Sound absorption lining: SBR/EPDM, black (see section "[RUBBER PROFILE SAL SBR/EPDM](#)" for technical data).

Tipo	Kg	Pezzi per confezione	Codice Articolo
12 - 15 mm ¼"	0.05	100	170693
15 - 19 mm 3/8"	0.06	100	170709
20 - 23 mm ½"	0.06	100	170718
25 - 28 mm ¾"	0.06	100	170727
32 - 35 mm 1"	0.07	100	170736
40 - 45 mm 1 ¼"	0.08	50	170745
48 - 52 mm 1 ½"	0.09	50	170754
52 - 58 mm	0.09	1	173360
60 - 64 mm 2"	0.1	50	170763
67 - 72 mm	0.19	1	173369
73 - 80 mm 2 ½"	0.2	25	170772
73 - 80 mm 2 ½"	0.2	25	116906
73 - 80 mm 2 ½"	0.2	25	170772B
86 - 91 mm 3"	0.22	25	170781
102 - 108 mm	0.25	1	173378
110 - 115 mm 4"	0.29	25	170790
110 - 115 mm 4"	0.29	25	116907
135 - 143 mm 5"	0.36	25	110884
149 - 161 mm	0.39	25	110885
162 - 170 mm 6"	0.39	25	110886