


FLAMCO CLEAN ECO-PLUS - prosystemitalia.com

FLAMCO CLEAN ECO-PLUS

- Group 2008A



Application

Removes solid particles that need to be flushed out before they can cause damage to the pump or water heater, for example.

Setting

For mounting in horizontal pipes.

Technical Data

Material: brass.

Maximum operating pressure: 10.0 bar.

Maximum supply temperature: 120 °C.

Minimum temperature: -10°C

Max % glycol: 50%

Maximum recommended flow velocity: 1.5 m/s.

Type	Joint	Capacity [litri]	Dimensions L x s x H [mm]*
Flamco Clean EcoPlus 22	22 mm	0,22	102 x 113 x 157
Flamco Clean EcoPlus 3/4	3/4" int.	0,22	102 x 113 x 157
Flamco Clean EcoPlus 1	1" int.	0,35	110 x 117 x 175,5
Flamco Clean EcoPlus 1 1/4	1 1/4" int.	0,48	116 x 121 x 196
Flamco Clean EcoPlus 1 1/2	1 1/2" int.	0,48	116 x 121 x 196
Flamco Clean EcoPlus 2	2" int.	0,75	125 x 135 x 258

Tipo	Kg	Pezzi per confezione	Codice Articolo
22mm	1.41	6	28635
3/4"	1.32	6	28630
1"	1.67	6	28631
1"1/4	2.2	6	28632
1"1/2	2.2	6	28633
2"	2.7	6	28634