



FLAMCOVENT SMART PN10 - prosystemitalia.com

FLAMCOVENT SMART PN10 - Group 2060C



Technical Specifications

With flanged connection according to EN 1092-1 PN16.

Maximum working pressure: 10 bar.

Models with a Maximum working pressure of 25 bar are available upon request.

Suitable for systems with a maximum flow temperature of 120 °C.

Suitable for glycol solutions of up to 50%.

In accordance with Pressure Equipment Directive 2014/68/EU.

DN	Capacity [L]	Ø [mm]	A [mm]	B [mm]	C [mm]	D [mm]	Kv * [m3/h] (delta P = 1 bar)
50	8	60,3	472	350	338	175	93
65	8	76,1	472	350	338	175	140
80	25	88,9	612	470	435	270	209
100	25	114,3	612	470	435	270	311
125	59	139,7	740	635	515	360	459
150	60	168,3	740	635	510	360	675
200	123	219,1	975	774	670	450	1340
250	287	273	1290	990	892	600	1952
300	333	323,9	1452	1006	1032	600	2830
350	646	355,6	1600	1214	1109	800	4084
400	731	406,4	1770	1220	1252	800	5866
500	1384	508	2096	1580	1470	1000	8387
600	2390	610	2492	1870	1760	1200	11939

Tipo	Kg	Pezzi per confezione	Codice Articolo
DN 50	14	1	31001
DN 65	16	1	31002
DN 80	25	1	31004
DN 100	29	1	31005
DN 125	48	1	31006
DN 150	52	1	31007

Tipo	Kg	Pezzi per confezione	Codice Articolo
DN 200	80	1	31008
DN 250	158	1	31009
DN 300	184	1	31010
DN 350	321	1	31011
DN 400	348	1	31012
DN 500	635	1	31013
DN 600	963	1	31014