

Prosystem Italia Srl

Via Friuli Venezia Giulia, 15
30030 Pianiga (VE) Italy
Tel. +39 041 5101622
Fax. +39 041 5131351

P. Iva 03470750278
Reg.Imp. Ve 03470750278
Cap. Soc. Euro 90.000,00
REA Padova n° 311219

www.prosystemitalia.com
info@prosystemitalia.com



AIRFIX A - prosystemitalia.com

AIRFIX A - Group 2013A



Application

For use in potable water or fresh water installations.

The inside of the Airfix vessel has a special coating which prevents oxidation. The composition of the diaphragm has been made for this range in such a way that there will be no variation in smell, colour or taste. The famous Flexcon clench ring construction allows the water section to be coated before assembly.

The Airfix A is fitted with a synthetic flow through device in a standard T-piece (included) which eliminates the formation of unwanted bacteria.

Technical Data

Max. working temperature: 70 °C (EN13831)

Max. working pressure: 8-10 bar

Pre-charge pressure: 4 bar

Approvals

- CE 0045 in according with PED 97/23/EC

- DVGW

- Accordant to European Directive 2002/16/CE

Tipo	Kg	Pezzi per confezione	Codice Articolo
8 L PN 10	3.7	50	24259
12 L PN 10	4.8	36	24349
18 L PN 10	5.9	24	24459
25 L PN 10	7.7	18	24559
35 L PN 8	9.7	18	24659
50 L PN 8	12.1	1	24749
80 L PN 8	15	12	24809