

Prosystem Italia Srl

Via Friuli Venezia Giulia, 15
30030 Pianiga (VE) Italy
Tel. +39 041 5101622
Fax. +39 041 5131351

P. Iva 03470750278
Reg.Imp. Ve 03470750278
Cap. Soc. Euro 90.000,00
REA Padova n ° 311219

www.prosystemitalia.com
info@prosystemitalia.com



SPLIT FLANGE 7012 PN16 - prosystemitalia.com

SPLIT FLANGE 7012 PN16 - Group 7012Z



Application

Connection to flange.

Technical data

Working pressure: 20 bar

Working temperature: from -34°C to +110°C with EPDM

Material:

- Body: spheroidal graphite cast iron according to ASTM A536 and ISO 1083
- Surface treatment: hot galvanized.
- Gasket: EPDM type E according to ISO 6182, FM 1920 and UL 213.

Bolts: tempered bolts, round head with oval neck. Heavy series nuts in carbon steel according to ASTM A183.

Approval

FM, UL.



Tipo	Kg	Pezzi per confezione	Codice Articolo
273,0 mm 10"	15.5	2	2278PN16273Z
	2	20	2278PN16060Z

Tipo	Kg	Pezzi per confezione	Codice Articolo
	2.55	15	2278PN16089Z
	5.17	7	2278PN16139Z
76,1 mm 2"½	2.49	16	2278PN16076Z
114,3 mm 4"	3.83	9	2278PN16114Z
168,3 mm 6"	6.85	6	2278PN16168Z
219,1 mm 8"	10.25	2	2278PN16219Z