

Prosystem Italia Srl

Via Friuli Venezia Giulia, 15
30030 Planiga (VE) Italy
Tel. +39 041 5101622
Fax. +39 041 5131351

P. Iva 03470750278
Reg.Imp. Ve 03470750278
Cap. Soc. Euro 90.000,00
REA Padova n ° 311219


www.prosystemitalia.com
info@prosystemitalia.com



SPRINKLER UPRIGHT - QUICK RESPONSE - RTI > 50 - prosystemitalia.com

SPRINKLER UPRIGHT - QUICK RESPONSE - RTI > 50

- Group 504



Application

Sprinkler pendent, made of brass, fast response, threaded connection 1/2 "and 3/4" K-factor 80 or 115 with glass bulb. Made for the jet directed downwards against the deflector.

Particularly suitable for dry systems.

Technical Data

Characteristics: spray sprinkler, pendent

Response sensitivity: fast RTI<50

Max working pressure: 12,0

Min request pressure: 0,68 bar

k factor: 80; 115

Material:

- Sprinkler body: brass (on request chrome-plated version)
- Deflector: brass (on request stainless steel version)
- Glass bulb: borosilicate glass
- Threaded pin: brass

Approvals

1/2" version: certified CE and FM.

3/4" version: certified CE.



Tipo	Kg	Pezzi per confezione	Codice Articolo
1/2" K80 57 °C	0	1	843060
1/2" K80 68 °C	0.2	1	843061
1/2" K80 79 °C	0.06	50	843062
1/2" K80 93 °C	0	1	843063
1/2" K80 141°C	0	1	843064
3/4" K115 57 °C	0	1	843070
3/4" K115 68 °C	0.06	1	843071
3/4" K115 79 °C	0	1	843072
3/4" K115 93 °C	0	1	843073
3/4" K115 141°C	0	1	843074