
Prosystem Italia Srl
Via Friuli Venezia Giulia, 15
30030 Pianiga (VE) Italy
Tel. +39 041 5101622
Fax. +39 041 5131351

P. Iva 03470750278
Reg.Imp. Ve 03470750278
Cap. Soc. Euro 90.000,00
REA Padova n ° 311219

www.prosystemitalia.com
info@prosystemitalia.com

UGELLO GETTO PIATTO A LAMA D'ACQUA - Group 510



Application

Create a horizontal or veticale jet as a fire wall. The flow change in according to the exit hole. To be installed in vertical or horizontal position.

Notes for project planning

For the design of this type of nozzle, the UNI 12845 is not expressed. For a indication of the size of these systems we refer to NFPA 13 (11.3.3 "Water curtains"), which decrees that the in a sprinkler the flat jet nozzles must ensure a flow of 37 l / min per linear meter; in the absence of sprinkler system,must be guaranteed a flow of 56.8 L / min.

Technical Data

Characteristics: Nozzle with blade water.

Attack: 1/2 "

Spray angle: 140°

Material: Brass.

Tipo	Kg	Pezzi per confezione	Codice Articolo
1/2'' K5	0.2	10	131240
1/2'' K7	0.2	10	131241
1/2'' K9	0.2	10	131242
1/2'' K11	0.2	10	131243
1/2'' K16	0.2	10	131244
1/2'' K18	0.2	10	131245

Tipo	Kg	Pezzi per confezione	Codice Articolo
1/2'' K22	0.2	10	131246
1/2'' K27	0.2	10	131247
1/2'' K31	0.2	10	131248
1/2'' K41	0.2	10	131249
1/2'' K52	0.2	10	131250
1/2'' K63	0.2	10	131251
1/2'' K95	0.2	10	131252