

Prosystem Italia Srl

Via Friuli Venezia Giulia, 15
30030 Pianiga (VE) Italy
Tel. +39 041 5101622
Fax. +39 041 5131351


P. Iva 03470750278
Reg.Imp. Ve 03470750278
Cap. Soc. Euro 90.000,00
REA Padova n ° 311219

www.prosystemitalia.com
info@prosystemitalia.com



PRESSURE SWITCH MOD. PMU-3 E PMU-10 - prosystemitalia.com

PRESSURE SWITCH MOD. PMU-3 E PMU-10 - Group 552



Application

Device that promptly reports the operation of activating remote alarm. Enables or disables other equipment. Equipped with Nc contact (normally closed) and Na (Normally Open). This device is adjustable pressure.

Technical Data

Temperature range: 0°C up to + 80°C water; - 25°C up to + 100°C compressed air

Voltage: Max 250V-AC/DC.

Operating pressure: Max 16 bar.

Material:

- Cover: PA trasparente;
- Diaphragm: CR with textile reinforcement;
- Housing: GD-Al Si12, sheet steel galvanized.

Approvals

Certificated VdS.



Tipo	Kg	Pezzi per confezione	Codice Articolo
PMU 3	0.2	1	792183
PMU 10	0.2	1	810564